

# PM3-SME SERIES

## PM3-15/35/45/55/60/65/75/100/120-SME

BATTERY CHARGERS  
 MAINTAINERS  
 INVERTERS  
 GENERATORS  
 DC POWER SUPPLIES  
 CONVERTERS  
 POWER CENTERS  
 AUTOMATIC TRANSFER SWITCHES  
 WATER PUMPS



### Features include:

- Adjustable voltage (13V–16V)
- Flexible charging: Fixed, 2-Stage, or 3-Stage Smart Charging
- Power options from 15A to 120A
- Easy-read LCD voltage display
- Quiet, temperature-controlled cooling fan
- Built-in overload & short-circuit protection
- Compact, mountable design with 120VAC input
- Maintenance-free operation
- 2-Year limited Warranty



MODEL #'S	PM3-35-SME	PM3-45-SME	PM3-55-SME	PM3-60-SME	PM3-75-SME	PM3-100-SME	PM3-120-SME
DC Output Voltage (no load) approx.	14.6/13.6/13.2V						
MAX AMP Output Continuous	35 amps	45 amps	55amps	60 amps	75 amps	100 amps	120 amps
MAX Power Output Continuous	510 watts	650 watts	800 watts	875 watts	1095 watts	1460 watts	1776 watts
MAX AC Current	8 amps	9 amps	11 amps	12 amps	13 amps	15 amps	15 amps
Typical Efficiency	>85%	>85%	>85%	>85%	>85%	>93%	>93%
Fan Control	Proportional						
Reverse Polarity, Overload & Thermal Protection	Yes						
Dimensions	7.8 x 10.5 x 3.5						
Weight	7.0 lbs	7.0 lbs	7.0 lbs	7.0 lbs	8.0 lbs	9.0 lbs	9.0 lbs

