

PMBC SE SERIES

PMBC-55/75/100/120-SE

BATTERY CHARGERS
 MAINTAINERS
 INVERTERS
 GENERATORS
 DC POWER SUPPLIES
 CONVERTERS
 POWER CENTERS
 AUTOMATIC TRANSFER SWITCHES
 WATER PUMPS



Features include:

- Adjustable output voltage: 13V–16V
- 100A power output with heavy-duty cables
- 3 charging modes: Fixed, 2-Stage, and 3-Stage Smart
- Easy-to-read LCD display
- Quiet, temperature-controlled cooling fan
- Built-in overload and short-circuit protection
- Maintenance-free rugged design
- Compact, easy-to-mount chassis
- 120VAC input for versatile use
- Backed by a 2-year Warranty



MODEL #'S	PMBC-55-SE	PMBC-75-SE	PMBC-100-SE	PMBC-120-SE
DC Output Voltage (no load) approx.	14.8V (Adjustable)	14.8V (Adjustable)	14.8V (Adjustable)	14.8V (Adjustable)
Output Amperage, Max Continuous	55 amps	75 amps	100 amps	120 amps
MAX Power Output Continuous	780 watts	1065 watts	1440 watts	1776 watts
MAX AC Current	7 amps	12 amps	13 amps	15 amps
Fan Control	Proportional	Proportional	Proportional	Proportional
Short Circuit, Over-temp, Reverse Polarity Protection	Yes	Yes	Yes	Yes
Fixed Output Range	13 to 16.5V	13 to 16.5V	13 to 16.5V	13 to 16.5V
Dimensions	7.5x10.5x3.45	7.8x9.5x3.5	7.15x11.5x3.48	7.15x11.5x3.48

